

NEW UPGRADES NOW STANDARD!

-LIGHTER ALUMINUM FRAME WORK-

-12.2 GAUGE CUT/ABRASION RESISTANT WIRE-

250 CFM PORTABLE AFTERCoolERS

ACSE250-12V-CH

CHICAGO INLET & CHICAGO OUTLET



ACSE250-12V-4P

4-PRONG INLET & 4-PRONG OUTLET



STANDARD SPECIFICATIONS:

- > CHICAGO AND 4-PRONG SET-UPS STANDARD
- > 40 MICRON AIR FILTER/SEPARATOR WITH A 1QT. RESERVOIR AND MANUAL DRAIN
- > 50 FEET OF 12.2 GAUGE CUT/ABRASION RESISTANT POWER CORD WITH CLAMPS
- > ALUMINUM CONSTRUCTED STAND, FIN GUARD, HANDLE AND PROTECTIVE CORD WRAP
 - > RATED 250 CFM OF AIRFLOW
 - > MAXIMUM PSI: 150PSI
- > SHIPPING/ASSEMBLED WEIGHT: APPROXIMATELY 55 POUNDS
- > APPROXIMATE DIMENSIONS ASSEMBLED: 36" w x 23" h x 14" d

OPTIONS:

- > ALTERNATIVE FITTINGS FOR INLET/OUTLET & BALL VALVES AVAILABLE
- > TWIST LOCK EXTENSION CORDS IN 50' AND 100' INCREMENTS
- > 120V AC TO 12V DC CONVERTERS