Part - RPT2AF/RPT2AC Compact - Lightweight



Part - RPT4AF/RPT4AC Wide Cutting Path



*All RPT tools are equipped with 1/4" NPT air inlet.

Novatek's versatile, high production Roto Peen/ Hand-Held Scarifiers are ideal for removing coatings from both steel and concrete surfaces. Quick change hubs with an assortment of abrasives enable rapid removal of mastics, alkyds to epoxy coatings while containing hazardous or non-hazardous dust.

Features

- Available in 2" or 4" models
- Offered with 3M Roto Peen flaps or carbon steel cutters
- Lightweight but powerful 1.2 hp air motor
- Rollers allow for use on curved surfaces
- Integrated vacuum shroud
- Compact design for tighter access
- Quick change hubs and abrasives
- Available in kit form
- 1.2 hp motor

Benefits

- 2" model is lighter and ideal for vertical and overhead use
- 4" model is best for horizontal surfaces
- High production rates
- Standard 1.5" vacuum port allows for dustless operation
- Converts in minutes to accept abrasive hubs for coating and material removal from concrete or steel
- Complies with OSHA and EPA standards easily when matched with our HEPA vacuums
- Replicates shot blast finish when equipped w/Roto Peen Flaps

<u>Model</u>	Part No.	Cutting Path	<u>Weight</u>	Length	<u>Width</u>	<u>Height</u>	<u>RPM</u>	<u>Air</u> Consum	<u>dBA</u> <u>Concrete/Steel</u>
2" Air w/ Flaps	RPT2AF	2.4" 60 mm	9.5 lbs 4.3 kg	14" 356 mm	6.25" 159 mm	6" 152 mm	3000	30 cfm 840 lpm	82-85
2" Air w/ Cutters	RPT2AC	2.4" 50 mm	13.1 lbs 6 kg	14" 356 mm	6.25" 159 mm	6" 152 mm	3000	30 cfm 840 lpm	87-96
2" Air RPT Kit	RPT2AK	2.4" 60 mm	9.5-13.1 lbs 4.3-6 kg	14" 356 mm	6.25" 159 mm	6" 152 mm	3000	30 cfm 840 lpm	82-96
4" Air w/ Flaps	RPT4AF	4.3" 110 mm	11 lbs 5 kg	14" 356 mm	9" 225 mm	6" 152 mm	3000	30 cfm 840 lpm	82-85
4" Air w/ Cutters	RPT4AC	4.3" 100 mm	16.7 lbs 7.6 kg	14" 356 mm	9" 225 mm	6" 152 mm	3000	30 cfm 840 lpm	87-96
4" Air RPT Kit	RPT4AK	4.3" 110 mm	11-16.7 lbs 5-7.6 kg	14" 356 mm	9" 225 mm	6" 152 mm	3000	30 cfm 840 lpm	82-96



www.novatekco.com +1-610-363-7800

16

Part - RPT2EF/RPT2EC Compact

Features

- 2" or 4" cutting path
- Powerful 1200 watt electric motor
- Dust-free when used with VSE-HEPA vacuum systems
- Integrated rollers
- Quick change hubs and abrasives
- Works up to 1.5" from walls
- Converts from Roto Peen flaps to cutter hubs in minutes (4" electric with cutters not available)

Benefits

- High production on decks, floors and walls
- Operates on standard 115 volt or 230 volt power
- Perfect for heavy coating removal
- High production on flat surfaces
- Works on curved surfaces and pipes
- Duplicates shot blast finish when equipped with Roto Peen flaps
- Complies with OSHA and EPA standards easily when matched with our HEPA vacuums





Part - RPT4EF Wide Cutting Path



*Electric RPT are also available equipped with 230 volt motor 50/60 Hz.

Model	Part No.	<u>Cutting</u> <u>Path</u>	<u>Weight</u>	<u>Length</u>	<u>Width</u>	<u>Height</u>	<u>RPM</u>	<u>Voltage</u>	<u>Power</u>	dBA Concrete/Steel
2" Electric w/ Flaps	RPT2EF	2.4" 60 mm	12 lbs 5.5 kg	20" 500 mm	8" 200 mm	9.5" 238 mm	3000	120 V 8 Amp	1200 W	82-85
2" Electric w/ Cutters	RPT2EC	2.4" 60 mm	16 lbs 7 kg	20" 500 mm	8" 200 mm	9.5" 238 mm	3000	120 V 8 Amp	1200 W	87-96
2" Electric w/ RPT Kit	RPT2EK	2.4" 60 mm	12-16 lbs 5.5-7 kg	20" 500 mm	8" 200 mm	9.5" 238 mm	3000	120 V 8 Amp	1200 W	82-96
4" Electric w/ Flaps	RPT4EF	4.3" 110 mm	14 lbs 6.4 kg	20" 500 mm	10.5" 260 mm	9.5" 238 mm	3000	120 V 8 Amp	1200 W	82-85

www.novatekco.com +1-610-363-7800



Roto Peen Tools

Roto Peen/Hand-Held Scarifier Kits

RPT Kits provide everything you need for a wide variety of applications. From concrete scarifying to light material removal, the RPT Kit will have you covered.



Includes

- Your choice of 2" or 4" Air or 2" Electric tool loaded with Roto Peen hub and "Type C" flaps
- Additional cutter hub loaded with carbon steel "star" cutters
- Rugged tool bag
- Applicable wrenches

Gear oil, (air model only)
(4" Electric Roto Peen unavailable in kit form)

*RPT also available in 230 volt motor	50/60 Hz.
---------------------------------------	-----------

<u>Model</u>	Part No.	Cutting Path	<u>Weight</u>	<u>Length</u>	<u>Width</u>	<u>Height</u>	<u>RPM</u>	<u>Air</u> Consum	<u>Air</u> Pressure	<u>Voltage</u>	<u>Power</u>	dBA Concrete/Steel
2" Air RPT Kit	RPT2AK	2.4" 60 mm	9.5-13.1 lbs 4.3-6 kg	14" 356 mm	6.25" 159 mm	6" 152 mm	3000	30 cfm 840 lpm	90 PSI	N/A	1.2 hp	82-92
4" Air RPT Kit	RPT4AK	4.3" 110 mm	11-16.7 lbs 5-7.6 kg	14" 356 mm	9" 225 mm	6" 152 mm	3000	30 cfm 840 lpm	90 PSI	N/A	1.2 hp	82-92
2" Electric w/ RPT Kit		2.4" 60 mm	12-16 lbs 5.5-7 kg	20" 500 mm	8" 200 mm	9.5" 238 mm	3000	N/A	N/A	120 V 8 Amp	1200 W	82-92

Part - RPTMRPC/RPTM212 (6 Pack of Flaps) Roto Peen Flaps

Duplicates shot blast finish



Applications/Features

- Coatings removal from steel or concrete, 20 to 25 mil removal
- Rust and scale removal
- Profiling and stress relief on steel
- Used to attain SSPC-SP 11 level of surface preparation
- Lightweight hubs dramatically decreases tool weight compared to cutter hub
- Duplicates a blasting profile
- Achieves 2 to 3 mil profile



www.novatekco.com +1-610-363-7800

Applications/Features

- Aggressive coatings removal and surface prep
- Mid-weight cutter bundle
- Rust and scale removal
- Heavy coatings removal, epoxy non skid
- Concrete preparation and scarifying
- Plaster and stucco removal
- Recommended for 25+mil removal

Part - RPTS210 (Star Cutter 80 Pack)

Part - RPTS200 Carbon Steel "Star" Cutters

Our most aggressive cutter



Part - RPTR200 Carbon Steel "Beam" Cutters Less aggressive cutter offers a long-life

Applications/Features

- Mid-level coatings removal, (Less aggressive than "Stars")
- Mid-weight cutter bundle
- Rust and scale removal
- Light concrete prep. and coatings removal
- Heavy coatings removal, epoxy non skid
- Concrete preparation and light resurfacing
- Plaster and stucco removal

Roto Peen hub complete

with pins 2" & 4"

• Recommended for 25+mil removal

Part - RPTR210 (Beam Cutter 60 Pack)

Part - RPTH276 / RPTH476

Part - RPTU278 / RPTU478

• Cutter hub replacement pins 2" & 4"



Part - RPTH278 / RPTH478

• Star hub complete with pins 2" & 4"





www.novatekco.com +1-610-363-7800



Novatek offers a range of Pneumatic and Electric HEPA Vacuums, specifically designed to work with our VSE product line. Choose between backpack, floor, or bulk collection units. Engineered for the recovery of lead, asbestos, mold, and other hazardous or non-hazardous materials.

Applications

- Use in difficult to access areas
- Perfect for attaching to scaffolding or boom trucks
- Haz Mat removal and recovery

Features & Benefits

- Your choice of powerful pneumatic or electric models
- Ultimate portability
- Perfectly matched to our VSE power tools
- 5 gallon steel recovery tank
- 4 stage filtration assures long HEPA life
- Can be converted from backpack to floor vac in seconds
- Individually tested and certified HEPA filters
- Air filter/dryer standard (pneumatic model only)
- Includes 6' x 1.5" of crush proof vacuum hose
- Integrated live air inlet with shutoff for connecting power tools



Air Backpack model with RotoPeen tool removing rust from a steel structure.



Model	Part No.	CFM Output Flow	Static Lift Inches of Water	<u>Air</u> Consumption	<u>Tank</u>	<u>Maximum</u> Hose Length
3 Gallon Air Backpack Vacuum	VA03ABK	170	160"	50 cfm @ 90 PSI 1420 lpm @ 6.2 bar	5 Gal 3 Gal Bag	75 ft. x 1.5"
3 Gallon Electric Backpack Vacuum	VA03EBK	110	110"	120 Volts, 60 Hz 11 Amps	5 Gal 3 Gal Bag	25 ft. x 1.5"

www.novatekco.com +1-610-363-7800



Part - VA03ABK **3 Gallon HEPA Air Backpack**



Part -VAO3EBK 3 Gallon HEPA Electric Backpack

HEPA Vacuums/ Accessories & Consumables



Moisture Filter Dryer Replacement cartridge



.

www.novatekco.com +1-610-363-7800

Floor Vac, Drum Adaptor

