

Atlas Copco Generators

Designed to perform, built to last.



QAS 330 (60 Hz)



Durability

- Rugged Zincor steel coated canopy.
- Mounted on rugged skids.
- Designed for extreme weather conditions.
- A standard sealed spillage-free frame, which will ensure that all fluids can be retained within the frame.

Efficiency

- Increased up-time: carefully selected components and tested configuration.
- Genuine versatility: QAS 330 can power a wide variation of critical applications.
- Reduced cost of ownership: 500 hrs service intervals, efficient transport handling.
- Designed for easy servicing.

Health, Safety and Environment

Atlas Copco's stringent manufacturing standards follow ISO 9001 quality assurance regulations. All components are produced and tested to exacting standards for optimum performance in the most demanding conditions.

Atlas Copco

Technical Data

Model	QAS 330
Rated Standby Power	280 kW / 350 kVA
Rated Prime Power	255 kW / 319 kVA
Voltage Selections 3Ø	208 / 240 / 480
Amperage Capacity @ 208 volts 3Ø	840 amps
Amperage Capacity @ 240 volts 3Ø	769 amps
Amperage Capacity @ 480 volts 3Ø	383 amps
Sound Pressure Level @ 23 feet @ 75% load	73 dB(A)
Fuel Tank Capacity (w/trailer)	426 gal.
Fuel Consumption @ 75% load	13.2 gl/hr
Fuel Autonomy @ 75% load (w/trailer)	32 hr

Engine	John Deere
Model	6090HF485
Rated Speed	1800 rpm
Emission Compliance	EPA Tier III
Rated Output	362 HP @ 1800 rpm
Coolant	Water / Glycol
Cylinders	6
Displacement	9 L
Engine Control	Electronic

Alternator	Mecc Alte
Model	ECO 38 2L/N
Degree Of Protection / Insulation Class	IP23 / H

Dimensions and Weight	
Dimensions Skid (L x W x H)	155.7 x 56.3 x 83.8 in.
Weight - Skid Wet	10,413 lbs
Dimensions w/trailer (L x W x H)	222.2 x 91.6 x 112 in.
Weight - w/trailer Wet	16,403 lbs

Convenience Receptacles	
1 x 20 amp	125 volt GFCI duplex
2 x 50 amp	125 / 250 volt twist lock

The information contained herein is general in nature and is not intended for specific construction, installation or application purposes.

Generator Features and Options Include

Multi-Voltage Selector Switch	●
Remote Start / Stop	●
Digital Control System	●
110% Fluid Containment	●
Oil Drain Pump	●
Skid-Mount	○
Battery Charger	○
Electronic Governor	●
Coolant Heater	●
Ball Coupling	○
Spare Tire	○
Rear Stabilizer Jacks	○
Tool Box	○
External Fuel Connections	●
4 Position Voltage Selector Switch	○
3 Position Voltage Selector Switch with 120/240 - 3Ø	○
	Option ○
	Standard ●



Control Panel

A comprehensive instrument panel enables all key operating functions to be supervised without opening the canopy. Analog gauges provide at-a-glance monitoring. Protected by a tough transparent cover, the single panel provides easy start up and control of the generator. The panel also provides full system monitoring to ease operation.

U.S. Sales/Distribution Center

Atlas Copco Compressors LLC
 1800 Overview Drive
 Rock Hill, SC 29730
 Tel. 803-817-7438
 Tel. 800-232-3234
 Fax. 803-817-7450
www.atlascopco.us

